



Version 2.1

Glass Mineral Wool with ECOSE® Technology



KNAUFINSULATION

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	1/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Knauf Insulation Glass mineral wool

Product name: Glass Mineral Wool with ECOSE® Technology

1.2. Relevant identified uses of the substance or mixture and uses advised against

<u>Identified use(s):</u> Thermal and/or acoustic insulation for use in technical applications, industrial applications and in building construction.

1.3. Details of the supplier of the safety data sheet

Head Office	Knauf Insulation Am Bahnhof
	97346 Iphofen
	Germany
	Tel:+32 (0) 1048 8460
	sds@knaufinsulation.com www.knaufinsulation.com
Country Contact:	UK
	Tel:+44 (0) 1744 766 666 tech@knaufinsulation.com

1.4. Emergency telephone number

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	2/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

<u>67/548/EEC:</u> The product is not classified.

GHS/CLP CE N°1272/2008	The product is not classified.
	The product is not blacomed.

2.2. Label elements

There are no Risk Phrases associated with this product.

The following sentences and

pictograms are printed on packaging:

The following sentences and pictograms are printed on packaging:







Ventilate working area if possible.



Rinse in cold water before washing.



Waste should be disposed of according to local regulations.



Clean using vacuum equipment.



Wear goggles when working overhead.

2.3. Other hazards

The mechanical effect of fibres in contact with skin may cause temporary itching.

Specific hazards: N/A.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	3/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

67/548/EEC:

<u>%:</u>	CAS-No.:	<u>EC No.:</u>	<u>REACH Reg.</u> <u>No:</u>	Chemical name:	Hazard classification:	<u>Notes:</u>
87-100	-	926-099-9	01-2119472313-	Glass Mineral Wool	-	(1), (2), (3)
0-13	-		-	Thermo set, inert polymer bonding agent derived from plant starches	-	

GHS/CLP CE N°1272/2008

<u>%:</u>	CAS-No.:	<u>EC No.:</u>	<u>REACH Reg.</u> <u>No:</u>	<u>Chemical name:</u>	Hazard classification:	<u>Notes:</u>
87-100	-	926-099-9	01-2119472313-	Glass Mineral Wool	-	(1), (2), (3)
0-13	-		-	Thermo set, inert polymer bonding agent derived from plant starches	-	
Notes:		e N 1 ((arth (CaO + MgO Note Q of directive 272/2008. 2) CAS-No.: Chem 3) Glass mineral w	an (machine) made vitreous + NaO + K2O) > 18 % in we 97/69/EEC and Classification nical Abstract Service vool insulation fibres are not 72/2008 (page 335 of the JC	eight meeting the requirer on, Labelling and Packagi classified carcinogenic a	nents of ng (CLP), ccording
			•	encapsulation materials: glas		

aluminium or Kraft paper or encapsulated in low density polyethylene (LDPE) and metallised LDPE film.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	4/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures		
Inhalation:	Remove from exposure. Rinse the throat and blow nose to clear dust.	
<u>Skin contact:</u>	If mechanical irritation occurs, remove contaminated clothing and wash skin gently with cold water and soap.	
Eye contact:	Rinse abundantly with water for at least 15 minutes.	
Ingestion:	Drink plenty of water if accidentally ingested.	

4.2. Most important symptoms and effects, both acute and delayed

The mechanical effect of fibres in contact with skin may cause temporary itching.

4.3. Indication of any immediate medical attention and special treatment needed

If any adverse reaction or discomfort continues from any of the above exposures, seek professional medical advice.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Water, foam, carbon dioxide (CO2), and dry powder.

5.2. Special hazards arising from the substance or mixture

Products do not pose a fire hazard in use; however, some packaging materials or facings may be combustible. Products of combustion from product and packaging - carbon dioxide, carbon monoxide and some trace gases such as ammonia, nitrogen oxides and volatile organic substances.

5.3. Advice for firefighters

In large fires in poorly ventilated areas or involving packaging materials respiratory protection / breathing apparatus may be required.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	5/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

<u>Personal precautions:</u> In case of presence of high concentrations of dust, use the same personal protective equipment as mentioned in section 8.

6.2. Environmental precautions

Environmental Not relevant. precautions:

6.3. Methods and material for containment and cleaning up

<u>Methods for cleaning up:</u> Vacuum cleaner or dampen down with water spray prior to brushing up.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Avoid unnecessary handling of unwrapped product.
Technical measures:	No specific measures. Cut using a knife, do not use a saw or use power tools.
Technical precautions:	Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:	To ensure optimum product performance; when packaging is removed or opened; products should be stored inside or covered to protect them from ingress of rain water or snow. Storage arrangements should ensure stability of stacked products and use on a first in first out basis (FIFO) is recommended. Delivered packed in polyethylene film and or on wooden pallets. No incompatible groups noted.
7.3. Specific end use(s)	

Specific use(s):

Not relevant.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	6/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure lim	<u>iits:</u>		•	ean level, refer vel, refer to me		-	-	
8.1. Control j	parameters							
UK: Glass	Mineral Wool							
Occupationa	l exposure limits:							
CAS-No.:	Chemical name:	A	<u>\s:</u>	Exposure I	<u>limits:</u>	<u>Type:</u>	Notes:	References:
-	Machine-made mine fibre (except for refra ceramic fibres and s purpose fibres)	actory		2 fibres/ml	5 mg/m3	TWA	-	EH40
8.2. Exposur	e controls							
Engineering	measures:	No spe	ecific requ	uirements. No	specific mea	asures.		
Respiratory e	<u>equipment:</u>	Wearing a face mask type in accordance with EN 149 FFP1 is recommended when using products in confined atmosphere or during operations which can generate emission of any dust.						
Hand protect	tion:	Use gl	oves to a	woid itching in	conformity v	vith EN 388.		
Eye protectio	on:	Use goggles especially if working above shoulders. Eye protection according to EN 166 is advised.						
Skin protection	on:	Cover	exposed	skin.				
<u>Hygiene mea</u>	asures:	After c	ontact, w	ash hands wit	h cold water	and soap.		

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	7/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance:	Solid.
<u>Form:</u>	Rolls., loose fibre, Panel.
<u>Colour</u>	Brown.
<u>Odour:</u>	Not relevant.
<u>pH:</u>	Not relevant.
Boiling point:	Not relevant.
Flash point:	Not relevant.
Flammability (solid, gas):	Not relevant.
Explosion limits:	Not relevant.
Relative density:	9 - 35 kg/m3
<u>Solubility:</u>	Generally chemically inert and insoluble in water.

9.2. Other information

Nominal diameter of fibres. : 3 - 5 µm

Length weight geometric mean diameter less 2 standard errors: < 6 μ m

Orientation of fibres: Random.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	8/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 10: STABILITY	SECTION 10: STABILITY AND REACTIVITY			
10.1. Reactivity				
Reactivity:	None.			
10.2. Chemical stability				
<u>Stability:</u>	Binder will decompose above 200°C.			
10.3. Possibility of hazardous	reactions			
Hazardous Reactions:	None in normal conditions of use.			
10.4. Conditions to avoid				
Conditions/materials to avoid:	Heating above 200 °C.			
10.5. Incompatible materials				
Incompatible materials:	None.			
10.6. Hazardous decomposition	on products			
Hazardous decomposition products:	None in normal conditions of use. Decomposition of binder above 200°C may produce carbon dioxide and some trace gases. The duration of release is dependant upon the thickness of the insulation, binder content and the temperature applied.			

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

The mechanical effect of fibres in contact with skin may cause temporary itching.

Classification not applicable for this product; in accordance with the directive 97/69/EC and European Regulation 1272/2008, nota Q. Weighted clearance half life of fibres, with length greater than 20µm after intra-tracheal instillation, is less than 40 days (result obtained from a test conform to the European protocol).

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	9/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 12: ECOLOGIC	AL INFORMATION
12.1. Toxicity	
Ecotoxicity:	This product is not ecotoxic to air, water or soil, by composition.
12.2. Persistence and degrad	<u>iability</u>
Degradability:	Inert inorganic product with Thermo set, inert polymer bonding agent derived from plant starches; 5 - 13%
12.3. Bioaccumulative potent	ial
Bioaccumulative potential:	Will not bio-accumulate.
<u>12.4. Mobility in soil</u>	
Mobility:	Not considered mobile. Less than 1% leachable organic carbon if landfilled.
	D
12.5. Results of PBT and vPv	<u>'B assessment</u>
Not relevant.	
12.6. Other adverse effects	

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues:	Dispose of in accordance with regulations and procedures in force in country of use or disposal.
Contaminated packaging:	Dispose of in accordance with regulations and procedures in force in country of use or disposal.
EWC-code:	17 06 04, Non-hazardous substance.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	10/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

<u>14.1. UN number</u>

UN-No:

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

Class:

14.4. Packing group

Packing group:

14.5. Environmental hazards

Marine pollutant: Environmentally Hazardous

substance:

14.6. Special precautions for user

Special precautions: None known.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk:

Not relevant.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	11/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The European Regulation on Chemicals No 1907/2006, Registration, Evaluation, Authorisation of Chemicals (REACH) enacted on June 1st 2007 requires the provision of Safety Data Sheet (SDS) for hazardous substances and mixtures / preparations.

Knauf Insulation mineral wool products (panels, batts or rolls), are defined as articles under REACH and therefore a Safety Data Sheet for these products is not a legal requirement.

In accordance with industry practice and voluntary commitments, Knauf Insulation has decided to continue to provide its customers with the appropriate information for the purpose of assuring safe handling and use of mineral wool throughout the product life.

This material Safety Data Sheet / Product Data Sheet is in accordance with the EU directives 67/548/EEC, 1999/45/EEC, 1907/2006, 1272/2008 and 453/2010.

15.2. Chemical Safety Assessment

CSA status: Not relevant.

Product name:	Glass Mineral Wool with ECOSE® Technology	Page:	12/12
Revision Date:	2013-08-06	Print date:	2013-08-06
Product No.:	KI_DP_101	SDS-ID:	GB-EN/2.1

SECTION 16: OTHER INFORMATION

All products manufactured by Knauf Insulation are made of non-classified fibres and are certified by EUCEB. EUCEB, European Certification Board of Mineral Wool Products - www.euceb.org, is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres, which comply with the exoneration criteria for carcinogenicity (Note Q) of the Directive 97/69/EC and the Regulation (EC) 1272/2008.

To ensure that fibres comply with the exoneration criteria all tests and supervision procedures are carried out by independent, expert qualified institutions. EUCEB ensures that the producers of mineral wool have put in place self-control measures.

The mineral wool producers commit to EUCEB to:

• supply sampling and analysis reports established by laboratories recognized by EUCEB, proving that the fibres comply with one of the four criteria of exoneration described in Note Q of the Directive 97/69/EC,

• be controlled, twice per year, of each production unit by an independent third party recognized by EUCEB (sampling and conformity to the initial chemical composition),

• put in place procedures of internal self-control in each production unit.

Products meeting EUCEB certification requirements can be recognised by the EUCEB logo printed on the packaging.

Further information can be obtained from: www.Eurima.org www.knaufinsulation.com

Moreover, in 2001, the IARC, reclassified glass mineral wool fibres from Group 2B (possibly carcinogenic) to Group 3 « agent which cannot be classified as for their carcinogenicity to humans». (See Monograph Vol 81, http://monographs.iarc.fr/).

	EUCEB
Product Families	: Earthwool Loft Rolls, Earthwool FactoryClad Rolls, Earthwool FrameTherm Rolls and Slabs, Earthwool Room-in-Roof Rolls, Earthwool Acoustic Rolls and Slabs, Earthwool Cavity Slabs, Earthwool Universal Slabs, Earthwool Duct Slab, Space Insulation, OEM Rolls and Slabs, Retail Loft Roll, Knauf Saver Value Triple Loft Insulation, Everyday Eco Loft Insulation, EKO Loft Rolls, Kalzip
Additional information:	Change to Sections: 16

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.