

Insulating Laminates

Knauf XPS Laminate Plus

Knauf insulating laminates provide an efficient way to achieve instant energy savings, while maximising room space. All Knauf Insulating Laminates offer simple solutions to meet the requirements of the Building Regulations for walls as well as room-in-roof situations for new build and refurbishment projects. Knauf insulating laminates reduce CO² emissions as well as reducing energy expenditure, offering short payback periods. Knauf insulating laminates are supplied with a tapered edge for direct decoration or plaster finish and can be installed using either Knauf Plasterboard Adhesive and mechanical fixings.

CFC and HCFC-free extruded polystyrene bonded to 9.5mm Knauf Wallboard offers an enhanced thermal performance at a reduced thickness with the additional advantage of providing good vapour resistance. Ideal for use in refurbishment, new build and warm roof situations where an enhanced level of thermal insulation is required.

Compliance: EN13950.



Tapered Edge

Dimensions (mm)			Material No.	Pallet Details		
Thickness	Width	Length		Boards	m ²	Tonnes (Approx.)
27	1200	2400	268262	36	103.7	0.71
35	1200	2400	268264	28	80.6	0.58
40	1200	2400	268265	25	72.0	0.53
45	1200	2400	268266	22	63.4	0.47
55	1200	2400	268267	16	46.1	0.36