

DECLARATION OF PERFORMANCE

Factory Control Certificate Number: 0013-CPD-537588

1. Product Group:

Type A – Pitch / Bitumen DPC Sheets

2. Unique Product Name / Code

Product name	Unique Identification Code	Nominal dimensions
Hyload Original DPC	31505000	20m x various widths

3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Linear damp proof course (DPC) bonded at joints.

4. Manufacturer: IKO PLC
Appley Lane North
Appley Bridge
Wigan
Lancashire
WN6 9AB

5. Authorised Representative: Not Applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of the CPR:

2+

7. Harmonised standard: EN 13969:2004

8. Notified Body: BSi

9. Declared Performance:

Essential Characteristic	Performance	Harmonised Technical Specification
Watertightness	2kPa for 24 hrs	EN 1928
Maximum tensile force	≥ 3 Mpa	EN 12311-1
Elongation	≥ 110%	EN 12311-1
Resistance to static loading	20kg (Concrete) 5kg (EPS)	EN 12730 (B)
Resistance to impact	500mm (Aluminium) 150 (EPS)	EN 12691
Resistance to tearing	Long ≥ 8.63N/mm	EN 12310-1
Flexibility at low temperature	≥ -15	EN 1109

Signed for and on behalf of the manufacturer by:



Terry Edwards
R&D and Quality Manager
Wigan, July 2013
