



ULTIMA+ dB



OFFICE – Trade Center Weena Plaza (NL)
ULTIMA+ dB SL2

ULTIMA+ dB not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides higher levels of sound attenuation performance for improving the privacy between adjacent spaces.

Key features

- Eliminates the need for sound barriers in closed offices
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee

Application areas

Ideal for individual / private offices.




Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	SL2
THICKNESS (mm)	19	19	19	23
MODULES (mm)	600 x 600 7688M 675 x 675 7689M 1200 x 600 7690M	600 x 600 7695M 675 x 675 7696M	600 x 600 7697M 675 x 675 7698M	1500 x 300 7691M 1800 x 300 7692M 2500 x 300 7693M
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar

COLOURS



Global White

SUSTAINABILITY



BRONZE



36-43¹








A+



E1


¹ Depends on thickness, edge detail and size of tile.

ACOUSTICS

	EN ISO 354 & EN ISO 11654			EN ISO 10848-2 & EN ISO 717-1			EN ISO 140-3 & EN ISO 717-1			Hz α_p					
	D_{nfw}	R_w	α_w	Class	NRC	125	250	500	1000	2000	4000				
• Board, Tegular, MicroLook 90	41 dB	21 dB	0.60(H)	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95				
• SL2	43 dB	-	0.60(H)	C	0.55	0.35	0.40	0.50	0.60	0.75	0.85				

FIRE REACTION




EEA Euroclass A2-s1, d0
EN 13501-1


RUS KM1 (G1, V1, D1, T1)
FZ 123

OTHER PERFORMANCES & FEATURES

87%




$\lambda = 0.067 \text{ W/m K}$




EN 12667 & ISO 8301


95% RH




7.6 kg/m²
(Board, Tegular, MicroLook 90)
9.1 kg/m² (SL2)






ISO 5




ISO 14644-1



30YEAR
system guarantee



CUSTOM OPTIONS



Dimensions