XTRATHERM® Product Health & Safety Information

RIGID POLYISOCYANURATE

SECTION 1: PRODUCT & COMPANY IDENTIFICATION

PRODUCT NAME: PIR Insulation

SYNONYMS: PIR

PRODUCT CODES: Thin R:

XT/CW Partial Fill Cavity Wall XT/CWP Partial Fill Cavity Plus XT/TL Thermal Liner (Dot & Dab) XT/TL/MF Thermal Liner (Mech Fix)

XT/TF Timber Frame XT/UF Underfloor XT/HYF Hyfloor XT/SK Sarking XT/WALK-R XT/PR Pitched Roof FR/ALU Flat Roof FR/MG Flat Roof FR/BGM Flat Roof FR/TP Thermal Ply TR/MG Tapered Roof TR/BGM Tapered Roof TR/ALU Tapered Roof

Xtroliner:

XtroWall

XO/UF Floor: Solid & Suspended

XO/FB Framing Board XO/SK Sarking XO/STP Soffit Plus XO/PR Pitched Roof

CavityTherm:

CT/PIR Cavity Therm

MANUFACTURER: Xtratherm UK Ltd.

ADDRESS: Park Road,

Holmewood Industrial Park,

Holmewood. S42 5UY, UK

PHONE: +44 (0) 371 222 1033 FAX: +44 (0) 371 222 1044 EMAIL: info@xtratherm.com WEBSITE: www.xtratherm.com

SECTION 2: HAZARDS IDENTIFICATION

No identified hazards

SECTION 3: PRODUCT COMPOSITION

CORE: Rigid thermoset urethane insulation (PIR) ref EN 13165

PRODUCT FACINGS: Laminate of foil/paper

Kraft paper

Mineral coated glass Bitumen coated glass WBP exterior grade plywood Gypsum plasterboard Resistant Magnesium Silicate

XTRATHERM® Product Health & Safety Information

RIGID POLYISOCYANURATE FOAM

SECTION 4: FIRST AID MEASURES

INHALATION: Dust is non-hazardous.

If dust is inhaled, person should get some fresh air

EYES: Dust should be removed by flushing with water

SKIN: Non-sensitizing.

When MG & BG are handled, some skin irritation may occur due to glass fibres

Ensure good hygiene is followed, after handling ensure skin is washed using soap/proprietary cleanser

INGESTION: No information available

OTHER: Seek medical attention if discomfort persists

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Water-Spray (Fog), Foam, CO², Dry Powder

FIRE AND EXPLOSION HAZARDS:

None Identified

Fire fighters should use SCBA gear.

Burning foam should be saturated with water.

Dust classification St Class 1 (weak explosion potential)

SECTION 6: ACCIDENTAL RELEASE MEASURES

Not Applicable

SECTION 7: HANDLING AND STORAGE

Products should be stored off the ground, on a clean, flat surface and under cover. Products should be stored in a location free from ignition hazards and direct radiant heat. The polythene wrapping is not considered adequate protection for outdoor storage. It is recommended that suitable PPE to be used in the handling and cutting of these materials.

To reduce dust it is recommended to use a trimming knife rather than a saw when cutting boards.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Dust is non-hazardous.

Dust from plasterboard / plywood facings may cause respiratory irritation.

It is recommended that a dust mask is worn when cutting.

In confined areas it is recommended that extraction is used when mechanical cutting is being performed.

HANDS: It is recommended that gloves are worn when handling product

EYE PROTECTION: Eye protection is recommended during mechanical cutting.

In bright sunlight, it is recommended to wear UV glasses when installing ALU/MG products

SKIN PROTECTION: Non- sensitizing.

To reduce the risk of cut hazard from edges of board it is advisable to wear general purpose gloves. In bright sunlight it is recommended to wear UV skin protection when installing ALU/MG products

OTHER: This product is non-load bearing.

The facings on ALU faced products can be slippy underfoot when wet

ISSUE DATE –July 2018 V1 PAGE 2 OF 3

XTRATHERM® Product Health & Safety Information

RIGID POLYISOCYANURATE FOAM

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Cream/ Buff coloured foam: either foil, mineral glass, bitumen, gypsum, timber, magnesium silicate facings.

ODOUR: Slight, non-offensive smell

pH: Neutral

FLASH POINT: Not Applicable

MELTING POINT: Not Applicable

FREEZING POINT: Not Applicable

PRODUCT DENSITY: 32kg/m³

SOLUBILITY IN WATER: Not Soluble

SECTION 10: STABILITY AND REACTIVITY

Product is stable and un-reactive under normal usage.

SECTION 11: TOXICOLOGICAL INFORMATION

Polyisocyanurate board is non-toxic and non-irritant.

SECTION 12: ECOLOGICAL INFORMATION

Product is inert and stable in water and soil.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste is non-hazardous

Waste product & packaging should be disposed of in accordance with local laws and regulations.

SECTION 14: TRANSPORT INFORMATION

Read section 7 in conjunction with this section Ensure load is secure before/during transit

Use mechanical lifting equipment when moving bulk quantities

SECTION 15: REGULATORY INFORMATION

Not Applicable

SECTION 16: OTHER INFORMATION

The information given in this sheet is based on our current knowledge of the product. It is given in good faith and refers only to those products named in this document. Xtratherm with-hold the right to update and amend this document as necessary The information should not be taken as a guarantee of performance. Users should conduct their own assessment and make applicable staff aware accordingly. For further assistance contact XtrathermTechnical Department.

ISSUE DATE – July 2018 V1 PAGE 3 OF 3