



DECLARATION OF PERFORMANCE TLX Silver MFTLXSILVERCPR			
1. Unique identification code of the product-type:	TLX Silver See product		
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:			
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	BS EN 13984:2013 Flexible sheets for waterproofing. Plastic and rubber vapour control layers. Definitions and characteristics		
4.Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Web Dynamics Ltd. Moss Lane Blackrod Bolton Lancashire BL5 5JB		
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	Not Relevant		
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	3		
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:	BTTG (NB 0338 & 0339) performed ITT under system 3 and issued test reports		
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	Not Relevant		



EN 13984:2013 Version No 2 September 2016





Essential Characteristics		Performance	
Property	Standard	Nominal	Notified body
Water tightness	EN 1928:2000, Method A	W1	BTTG
Resistance to impact	EN 12691	NPD	-
Water vapour resistance after artificial ageing resistance	EN 1296 (artificial ageing) EN 1931	Sd >74.05m* μ>300,000*	BTTG
Chemical resistance	EN 1847	NPD	-
Resistance to tearing	12310-1	MD: 167N CD: 217N	BBA
Joint Strength	EN 12317-2	NPD	-
Water vapour resistance	EN 1931	Sd >66.70m* μ>300,000*	BTTG
Tensile Properties	EN 12311-2	MD: 510N/50mm CD: 470N/50mm	BTTG
Reaction to fire	EN 13501- 1:2007+A1:2009	Class D	BTTG
Dangerous substances	-	NPD	

^{*} Figure quoted for 1 external, reflective layer (WEB 1B) only. Actual product performance will be greater than this due to 2nd outer layer and 4 metalised internal layers

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Tim Woodbridge

Bolton, United Kingdom 29/09/2016

Managing Director