

PRODUCT TECHNICAL INFORMATION SHEET

PRODUCT NAME : SANDBLAST BUFF (73MM)
REF. CODE : 24167160
DESCRIPTION : BUFF MULTI
MANUFACTURE : EXTRUSION
APPEARANCE : WIRECUT - DRAGFACE
- GRITTY
CONFIGURATION : PERFORATED - 3 HOLES (VERTICAL)
REAR FACE - SMOOTH
WORK SIZE * : 215 x 102 x 73

GUARANTEED PROPERTIES EN771-1: 2003

COMPRESSIVE STRENGTH : MIN. 40N/mm²
WATER ABSORPTION : MAX. 20%
DURABILITY DESIGNATION : F2
ACTIVE SOLUBLE SALTS : S2
SIZE TOLERANCE * (/ RANGE) : T2- R1
GROSS DENSITY (Tolerance) : 1450Kg/m³ (D1)
NET DENSITY (Tolerance) : 2100Kg/m³ (D1)
THERMAL CONDUCTIVITY ($\lambda_{10, dry}$) : P=90% 0.69W/m.K
INITIAL RATE OF WATER ABS. : 2.0Kg/m².minute
BOND STRENGTH (General Mortar) : 0.15N/mm² (fixed value)
REACTION TO FIRE : Class A1
WATER VAPOUR PERMEABILITY (μ) : 5/10 (tabulated)
PACK QUANTITY - SIZE : 412 no - 900 x 900 x 950 H
TYPICAL PACK WEIGHT : 973 Kg
PACKAGING : Shrink Wrapping [YES] Pallet [NO]
BATCH IDENTIFICATION : Shrink Wrapping [YES] Product [YES]
ADDITIONAL FEATURES : Quality (Kitemark) Certified [YES]
: Packaging – CE Marked [NO]