

# TECHNICAL DATA SHEET

## TRAVIS PERKINS ALL PURPOSE POWDER FILLER

Travis Perkins Powder Filler is easy to mix and simple to use. It does not shrink and has excellent adhesive properties which keeps the filler firmly in position. Easy sanded, giving a smooth surface which will take nails and screws when set. Suitable for exterior use providing it is sealed with paint or varnish, when dry.

### USES

Travis Perkins Powder Filler is specially formulated for repairs to plaster, plasterboard, wood, brick, stone and most other building materials. Ideal for preparing surfaces before painting or wallpapering. Use filler to fill cracks and holes in walls, ceilings and round doorframes and skirting boards. The filler gives a smooth surface perfect for wallpapering or painting.

**COLOURS:** White to off-white

**PACKAGING:** 1.8kg packed 1 x 6

### PREPARATION

Mix Travis Perkins Filler with cold water to make a stiff paste. Approximately 2½ parts filler to one part cold water. Use a thicker mix for deep cracks/ holes. Always mix in a clean container. Brush out loose material and dust from crack or hole to be filled.

### APPLICATION

Apply filler with trowel or knife and press firmly into cavity. Smooth off slightly proud of surface and when dry, rub down with sandpaper. Travis Perkins Filler stays workable for 1¼ hours after mixing.

### FINISHING

Dries white. Can be overpainted or papered, without priming. For exterior use ensure the filler is sealed with paint or varnish. All tools and mixing bowls should be cleaned with warm water before filler sets. Dirty tools can shorten setting times.

### HEALTH & SAFETY

This product is safe in normal use. Wash off the skin with soap and water. Keep out of eyes. Keep away from children and animals.

## TRAVIS PERKINS ALL PURPOSE POWDER FILLER TECHNICAL DATA SHEET

### LIMITATIONS

An adhesion test prior to application is recommended. It is the users responsibility to determine suitability.

### LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Siroflex Limited cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability of use.

### TECHNICAL DATA

#### Specification

Composition	A specially formulated filler containing gypsum minerals, plaster, calcium magnesium carbonate, binders and set time modifiers.
Physical state	Dry fine powder
Form/ colour	White to off white
Odour	Nil
Flammability	Non Flammable
pH	6.5 – 7.8 (280g powder to 120g water)