Serie | 2, Wall-mounted cooker hood, 90 cm, clear glass black printed DWK095G60B

C

RimVentilation

Optional accessories

DWA0LK6A : Standard odor filter

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- An impressive extraction rate of 629 m3/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.

Technical Data

Typology :	Chimney
Approval certificates :	CE
Length of electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	354
Minimum distance above an electric hob :	470
Minimum distance above a gas hob :	570
Net weight (kg) :	18.108
Type of control :	Electronic
Number of speed settings :	3
Maximum output air extraction (m3/h) :	629
Number of lights (Stck) :	2
Noise level (dB(A) re 1 pW) :	67
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242005176106
Connection rating (W) :	216
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation type :	Wall-mounted

4 242005 176106

Serie | 2, Wall-mounted cooker hood, 90 cm, clear glass black printed
DWK095G60B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key performance features:

- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Maximum extraction rate exhaust air 629 m^3/h according to EN 61591
- Noise max. Normal Level: 67 dB*
- TouchControl with Electronic display
- 3 power levels
- 2 x LED lights
- Colour Temperature: 3000 K
- 2 removable metal grease filter cassettes
- Designed for wall mounted installation
- Rim ventilation

Design

- Black glass canopy
- angled glass design
- Chimney extractor hood
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 629 m^3/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 67 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 67 dB (A) re 1pW
- Noise max. Normal Level: 67 dB*
- Power rating: 216 W
- Light Intensity: 377 lux
- Colour Temperature: 3000 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 750-1080 x 896 x 386 mm
- Dimensions recirculating (HxWxD): 862-1080 x 896 x 386 mm
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 94.5 kWh/year*

Optional accessories

- Recirculating kit

** In accordance with the EU-Regulation No 65/2014*