

## SAFETY DATA SHEET

### 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE  
**Product number** 894298 Yellow, Red and White

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** 4TRADE  
 Lodge Way House  
 Lodge Way  
 Harlestone Road  
 Northampton  
 NN5 7UG  
 www.4tradeproducts.co.uk

**Contact person** Sales Department -, 08.00 - 17.00 hrs Mon - Fri.

##### 1.4. Emergency telephone number

**SDS No.** 11293

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Aquatic Chronic 3 - H412

**Classification (67/548/EEC or 1999/45/EC)** Xi;R36. F+;R12. R52/53,R66,R67.


**Human health** Gas or vapour is harmful on prolonged exposure or in high concentration. Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Deliberately concentrating and inhaling contents of this container is dangerous and can be fatal.

**Environmental** This product does not contain substances which are harmful to aquatic organisms or which may cause long term effects to the aquatic environment

**Physicochemical** Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Do not pierce or burn even after use.

##### 2.2. Label elements

###### Pictogram



**894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE**

<b>Signal word</b>	Danger
<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe vapour/ spray. P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P314 Get medical advice/ attention if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
<b>Supplemental label information</b>	EUH066 Repeated exposure may cause skin dryness or cracking.
<b>Contains</b>	ACETONE, BUTYL ACETATE -norm, AROMATIC HYDROCARBON
<b>Supplementary precautionary statements</b>	P273 Avoid release to the environment. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P337+P313 If eye irritation persists: Get medical advice/ attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

**2.3. Other hazards**

This product does not contain any substances classified as PBT or vPvB.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

<b>ACETONE</b>	<b>30-60%</b>
CAS number: 67-64-1	EC number: 200-662-2
	REACH registration number: 01-2119471330-49-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
<b>PROPANE</b>	<b>10-30%</b>
CAS number: 74-98-6	EC number: 200-827-9
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Gas 1 - H220	F+;R12

**894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE**

<b>BUTANE</b>		<b>10-30%</b>
CAS number: 106-97-8	EC number: 203-448-7	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12	
<b>SOLVENT NAPHTHA, LIGHT AROMATIC( content of benzene &lt;0.1%)</b>		<b>5-10%</b>
CAS number: 64742-95-6	EC number: 265-199-0	REACH registration number: 01-2119455851-35
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.	
<b>ISOBUTANE</b>		<b>5-10%</b>
CAS number: 75-28-5	EC number: 200-857-2	
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12	
<b>AROMATIC HYDROCARBON</b>		<b>1-5%</b>
CAS number: 95-63-6	EC number: 202-436-9	
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 Xn;R20 Xi;R36/37/38 N;R51/53	
<b>BUTYL ACETATE -norm</b>		<b>1-5%</b>
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-0000
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 R66 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

**General information** Move affected person to fresh air at once.

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation persists after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Get medical attention promptly if symptoms occur after washing.
<b>Inhalation</b>	Vapours may cause drowsiness and dizziness.
<b>Ingestion</b>	Drowsiness, dizziness, disorientation, vertigo.
<b>Skin contact</b>	Prolonged skin contact may cause redness and irritation.
<b>Eye contact</b>	May cause severe eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Water spray, foam, dry powder or carbon dioxide.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Pressurised container: Must not be exposed to temperatures above 50 °C. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
<b>Hazardous combustion products</b>	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Use water spray to reduce vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray and remove container, if no risk involved.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Ensure suitable respiratory protection is worn during removal of spillages in confined areas.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Avoid discharge into drains.
----------------------------------	------------------------------

### 6.3. Methods and material for containment and cleaning up

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13. See Section 11 for additional information on health hazards.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray mists. Do not spray near naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Extremely flammable. Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn even after use.

**Storage class** Extremely Flammable Aerosol.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### PROPANE

Long-term exposure limit (8-hour TWA): Asphyxiating Asphyxiating

Short-term exposure limit (15-minute): Asphyxiating Asphyxiating

##### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Carc

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### SOLVENT NAPHTHA, LIGHT AROMATIC( content of benzene <0.1%)

Long-term exposure limit (8-hour TWA): SUP 600 mg/m<sup>3</sup>

##### ISOBUTANE

Long-term exposure limit (8-hour TWA): WEL 800 ppm

Short-term exposure limit (15-minute): WEL 800 ppm

##### AROMATIC HYDROCARBON

Long-term exposure limit (8-hour TWA): WEL 25 ppm 125 mg/m<sup>3</sup>

##### BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

**Ingredient comments** SUP = Supplier's recommendation.

### ACETONE (CAS: 67-64-1)

<b>DNEL</b>	Consumer - Oral; Long term : 62 mg/kg/day Consumer - Dermal; Long term : 62 mg/kg/day Industry - Dermal; Long term : 186 mg/kg/day Consumer - Inhalation; Long term : 200 mg/m <sup>3</sup> Industry - Inhalation; Short term : 2420 mg/m <sup>3</sup> Industry - Inhalation; Long term : 1210 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 10.6 mg/l - Marine water; 1.06 mg/l - Intermittent release; 21 mg/l - Soil; 29.5 mg/l - Sediment (Marinewater); 3.04 mg/kg - Sediment (Freshwater); 30.4 mg/kg

### SOLVENT NAPHTHA, LIGHT AROMATIC( content of benzene <0.1%) (CAS: 64742-95-6)

<b>DNEL</b>	Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 32 mg/m <sup>3</sup> Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day
-------------	--

### BUTYL ACETATE -norm (CAS: 123-86-4)

<b>DNEL</b>	Workers - Inhalation; Short term systemic effects: 960 mg/m <sup>3</sup> Workers - Inhalation; Long term systemic effects, local effects: 480 mg/m <sup>3</sup> Consumer - Inhalation; Short term systemic effects: 859.7 mg/m <sup>3</sup> Consumer - Inhalation; Long term systemic effects: 102.34 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 0.18 mg/l - Marine water; 0.018 mg/l - Intermittent release; 0.36 mg/l - Sediment (Freshwater); 0.981 mg/kg - Sediment (Marinewater); 0.0981 mg/kg - Soil; 0.0903 mg/kg

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

### Personal protection

When using do not smoke.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

<b>Hand protection</b>	To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Butyl rubber. Thickness: > 0.3 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent reasonably probable skin contact.
<b>Hygiene measures</b>	When using do not eat, drink or smoke. Wash promptly if skin becomes contaminated.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. It is recommended to use respiratory equipment with combination filter, type A2/P2.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Various colours
<b>Odour</b>	Organic solvents.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Technically not feasible.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	Not determined.
<b>Flash point</b>	< -40°C Closed cup.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Flammability (solid, gas)</b>	Not determined.
<b>Upper/lower flammability or explosive limits</b>	: 1.8
<b>Other flammability</b>	Not determined.
<b>Vapour pressure</b>	Not determined.
<b>Vapour density</b>	heavier than air
<b>Relative density</b>	1.01 @ @ 20 C°C
<b>Solubility(ies)</b>	Immiscible with water
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	410 - 580°C
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	Not applicable.

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

<b>Explosive properties</b>	Not determined.
<b>Explosive under the influence of a flame</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Not determined.
<b>Comments</b>	Information given is applicable to the major ingredient.

### 9.2. Other information

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

**Reactivity** There are no known reactivity hazards associated with this product.

##### 10.2. Chemical stability

**Stability** Highly volatile.

##### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not determined.

##### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

##### 10.5. Incompatible materials

**Materials to avoid** Strong acids. Strong alkalis. Strong oxidising agents.

##### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

###### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 180,000.0

**ATE inhalation (vapours mg/l)** 440.0

**ATE inhalation (dusts/mists mg/l)** 60.0

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

**Inhalation** Harmful by inhalation.

**Ingestion** Harmful: may cause lung damage if swallowed. Drowsiness, dizziness, disorientation, vertigo.

**Skin contact** Harmful in contact with skin. Prolonged and frequent contact may cause redness and irritation.

**Eye contact** Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting.



## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

<b>Acute and chronic health hazards</b>	Vapours in high concentrations are narcotic. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Arrhythmia, (deviation from normal heart beat).
<b>Route of exposure</b>	Inhalation Skin and/or eye contact.
<b>Target organs</b>	Central nervous system Respiratory system, lungs
<b>Medical symptoms</b>	Narcotic effect. Vapours may cause drowsiness and dizziness.

### Toxicological information

#### SECTION 12: Ecological Information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

##### 12.1. Toxicity

**Toxicity** Dangerous for the environment if discharged into watercourses

##### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

##### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No information available.

**Partition coefficient** Not determined.

##### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product contains substances which may accumulate in sediment.

##### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

##### 12.6. Other adverse effects

**Other adverse effects** None known.

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

**General information** Do not puncture or incinerate even when empty.

**Disposal methods** Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** Empty Aerosol: 15 01 10 (Containing hazardous residues). Full or Partially Empty Aerosol: 16 05 04. Empty Aerosol: 15 01 04 (No hazardous residues).

#### SECTION 14: Transport information

**General** This product is packed in accordance with the Limited Quantity Provisions of CDG CPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID class	2, 5F
ADR/RID label	2.1
IMDG class	2
ICAO class/division	2
ICAO subsidiary risk	2.1

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	#
IMDG packing group	#
ICAO packing group	#

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-D, S-U
Tunnel restriction code	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

## 894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE

<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

<b>Abbreviations and acronyms used in the safety data sheet</b>	ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. GHS: Globally Harmonized System. IATA: International Air Transport Association. ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. UVCB - Unknown or variable composition, complex reaction products or Biological materials. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. vPvB: Very Persistent and Very Bioaccumulative. EC <sub>50</sub> : 50% of maximal Effective Concentration.
<b>Classification abbreviations and acronyms</b>	Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Eye Dam. = Serious eye damage Carc. = Carcinogenicity Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Press. Gas (Liq.) = Gas under pressure: Liquefied gas Skin Irrit. = Skin irritation Skin Sens. = Skin sensitisation STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure
<b>Revision comments</b>	Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830
<b>Issued by</b>	Technical Dept. (P.E.)
<b>Revision date</b>	13/04/2018
<b>Revision</b>	4.0

**894298 - 4 TRADE LINE MARKING PAINT AEROSOL - YELLOW, RED AND WHITE**

<b>Supersedes date</b>	06/07/2015
<b>SDS number</b>	11293
<b>SDS status</b>	Approved.
<b>Risk phrases in full</b>	R10 Flammable. R11 Highly flammable R12 Extremely flammable. R36 Irritating to eyes. R37 Irritating to respiratory system. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.
<b>Signature</b>	Initials_____

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.