

TECHNICAL DATA SHEET

TDS: CVQ108

ROAD LINE MARKING AEROSOL PAINT

141/Q108/ ALL

DESCRIPTION:

Coo-Var Road Line Marking Aerosol Paint is a fast drying line marking aerosol for use on many surfaces. Available in six colours.

RECOMMENDED USE:

Coo-Var Road Line Marking Aerosol Paint is ideal where speed and efficiency are important. Convenient, fast line marking system for car parks, tennis courts, building sites, factories, schools and quick 'site' markings. Appropriate for a variety of surfaces both indoor and outdoor including bitumous, tarmacadam and concrete. Ideal for use with coo-Var stencils for general markings. For a stockist call 01482 328 053

AVAILABILITY:

750ml Aerosol

FINISH:

Matt

COLOUR:

White, Yellow, Blue, Red, Green and Black

TYPICAL S.G. (SPECIFIC GRAVITY):

N/A

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

DRY FILM THICKNESS D.F.T

EXPECTED SPREADING RATE:

Please see Remarks section.

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

<-40 °C (closed cup)

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: 15 - 30 mins @ 20 °C

Hard dry: 2 hours @ 20 °C

Full hardness:

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

2 hours

APPLICATION SPECIAL CONDITIONS:

Caution - When applying over other floor coatings, check a small area first for compatibility.

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A restrictions

Method: Invert can to use.

Thinner N/A
(Max vol):

Nozzle size: N/A

Nozzle N/A
pressure:

Cleaning N/A
solvent:

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-VAR

Email: info@coo-var.co.uk

www.coo-var.co.uk

Recoat 2 hours
interval:

SURFACE PREPARATION:

Ensure all surfaces are clean, dry and free from grease, oil and any other contaminants.

MIXING INSTRUCTIONS:

Shake the can for a minimum of 1 to 2 minutes after the agitator balls are heard rattling and again frequently during use. **IMPORTANT** - After use do not allow paint to dry in the nozzle by turning the can so it points upwards and pressing the nozzle for a few seconds to clear the nozzle.

APPLICATION CONDITIONS:

Best when used with an applicator, speed of movement dictates the density of the line produced. Do not apply if ambient temperatures fall below 3 degree C or relative humidity exceeds 90%.

PRECEDING COAT:

N/A

SUBSEQUENT COAT:

Coo-Var Road Line Aerosol Paint

REMARKS:

60 to 100m long x 50mm wide line depending on application weight.

Storage, it is advisable to store the aerosols on their sides to prevent blocking.

HEALTH AND SAFETY:

See safety data sheet - SDS 10773

ISSUED:

20 May 2009

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"