

## CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE

**DoP Number:**

FS911

**1. Unique identification code of the product-type:**

FS911 76mm Heavy Duty Tubular Mortice Latch

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:**

FS911 76mm Heavy Duty Tubular Mortice Latch

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**

Firestop Manufacturing Ltd, Unit 4-6 Wyvern Buildings, Grove Trading Estate, Dorchester, Dorset, DT1 1ST, United Kingdom

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

N/A

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 1

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard.**

EN 12209:2003 incorporating Corrigendum No 1 Notified product certification body No. 1221 performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and evaluation of factory production control; and issued the certificate of constancy of performance of the product.

**8. European Technical Assessment:**

N/A

## 9. Declared performance

Essential Characteristic	Performance	Harmonised technical specification
Self closing		
5.4.2 Closing force	Grade 7, up to 100 kg door mass, 15 N max. closing force	EN 12209: 2003 incorporating Corrigendum No. 1
5.1.2 Re-latching force of latch bolt	Greater than 2.5 N	
Essential characteristic	Performance	Harmonised technical specification
Durability of self closing		
5.3.1 Durability of latch action	Grade A, 50,000 test cycles, 0 N load on latch bolt	EN 12209: 2003 incorporating Corrigendum No. 1
Ability to maintain the door in the closed position and not contribute to the spread of fire	Grade 1	
Dangerous Substances Annex ZA3	The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Mr Keith Sutcliffe**  
**Managing Director**

Date of issue: 25/01/2018

**Firestop Manufacturing Ltd**  
**Unit 4-6 Wyvern Buildings**  
**Grove Trading Estate**  
**Dorchester, Dorset, DT1 1ST**  
**United Kingdom**

Office: 01305 257428

