



Cyan



Magenta



Yellow



Black

130mm

**BARCODE  
HERE**

**SAFETY & PRECAUTIONS**

- › Wear protective clothing and work in well-ventilated conditions.
- › If product enters the eyes, wash thoroughly with water and seek medical advice.
- › May cause skin irritation to sensitive skin.

www.pavetuf.co.uk For further information or technical advice call 0845 072 1150

Distributed worldwide by Natural Paving Products (UK) Ltd  
www.naturalpaving.co.uk

Jointing Compound available in  
**Black** **Grey** **Buff**

**6 EASY STEPS TO GREAT LOOKING PAVING**

- 1) Thoroughly pre-soak the area before application. The more water used the better the result.
- 2) Pour Pavetuf Jointing Compound evenly across your newly laid paving.
- 3) Using a stiff broom, brush the sand into the joints ensuring that they are completely filled.
- 4) Repeat this process until all joints have been filled.
- 5) Ensure that the surface of the paving and sand are kept wet during the application of Pavetuf Jointing Compound.
- 6) Top up any joints that haven't been filled properly and wash off the excess sand from the surface using a watering can or hosepipe with a low water pressure.

**CURING**  
Curing in warm dry conditions will take approximately 18-24 hours. Do not allow Pavetuf Jointing Compound to dry on the surface of the paving. We recommend you then seal your paved area with Pavetuf Sealer.

**STORAGE**  
Any unused product can be kept in the tub. Add sufficient water to cover the surface of the remaining product. Store in a cool, dry and frost-free area at temperatures between 5°C and 30°C. Pour off excess water before re-use. Be sure to use within 2 years of the date shown on the tub.

**COVERAGE**  
A 15kg bucket will cover approx. 7m<sup>2</sup> of paving (based on 450mm x 450mm slabs with 25mm x 8mm joint width). A Natural Paving 600 Series 15.25m<sup>2</sup> Project Pack will require approx. 2 tubs of Pavetuf Jointing Compound.

**PREPARATION**  
Before starting please ensure that the area to be jointed can be drained of water. Pavetuf Jointing Compound is suitable for use with most paving types, apart from block paving, however some paving can be prone to staining. Before applying, test a small area first to ensure your paving does not discolour. For more information on preparing your paving for Pavetuf Jointing Compound, please visit pavetuf.co.uk. If applying in temperatures below 0°C please use the dry mix application method. You can also contact the technical team for further advice on 0845 072 1150.

**ADDED FEATURES & BENEFITS**

- ✔ Can be used in all weathers
- ✔ Can be applied all year round at temperatures as low as -5°C
- ✔ Easy to apply
- ✔ No waste – can be re-used
- ✔ ECO-friendly
- ✔ Durable
- ✔ Inhibits weed growth
- ✔ Can be applied to paving with joint widths as narrow as 3mm and with minimum depths of 25mm

Colour of lid denotes colour of compound

Jointing Compound  
**15** KG

**The all weather jointing compound**

Jointing Compound available in  
**Black** **Grey** **Buff**

- Apply in all weathers
- Apply with water
- Walk on in 18-24 hours
- 7m<sup>2</sup> coverage

165mm

130mm

270mm

130mm

270mm

1020mm