

INTRODUCING THE NEW

# XI RANGE



 Paslode®

GAS FRAMING NAILER



## 360Xi

TOOL PRODUCT CODE:  
**019700**

The 360Xi framing nailer is light and perfectly balanced to guarantee a great performance for multiple applications. A high performing lithium battery and a weatherproof fuel cell ensures the tool will run all day, every day no matter the challenge.

### IDEAL USERS

Carpenters or Joiners working on New Build and Renovation projects.



FEATURE




BENEFIT

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>● Unbeatable power to weight ratio</li> <li>● Lighter and better balanced tool: 3.6kg</li> <li>● Quick release magazine</li> <li>● New battery position for high performing battery</li> <li>● Re-engineered grip</li> </ul> | <ul style="list-style-type: none"> <li>● Able to drive long nails into the hardest of substrates</li> <li>● Guarantees all day productivity</li> <li>● Designed to make nail jams a thing of the past</li> <li>● Ensures your tool will work all day. Every day.</li> <li>● Ensures extra comfort and convenience</li> </ul> |
|---|--|

### DID YOU KNOW:

The Paslode No-mar Cladding probe is available as an interchangeable accessory.



CONSUMABLES

BS 5534  
British Standard

### EUROCODE 5 SERVICE CLASS

- All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

### CORROSION REQUIREMENTS OUTLINED IN EUROCODE 5

Service Class 1 INDOORS	Service Class 2 INDOORS NOT HEATED, OUTDOORS PROTECTED	Service Class 3 OUTDOORS, EXPOSED TO WEATHER
BRIGHT		
ELECTRO GALV ≥ 12µm and GALV-PLUS® ≥ 15µm		
HOT DIPPED GALVANISED ≥ 55µm		
STAINLESS STEEL - A2 & A4 (AISI 304)		

- All Paslode nails are hexavalent chromium, cadmium and lead free
- Technical documentation available via the website - [www.paslode.co.uk](http://www.paslode.co.uk)

**360Xi requires Paslode 2.8 or 3.1mm RoundDrive nails. Available in sizes from 51-90mm**

### 360Xi NAIL SELECTION GUIDE

NAIL	QTY	CODE	APPLICATIONS	Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
51 x 2.8mm Ring	3300	141083		●										
63 x 2.8mm Ring	3300	141078		●										
75 x 3.1mm Ring	2200	141081			●	●								
90 x 3.1mm Smooth	2200	141076			●	●	●							
90 x 3.1mm Ring	2200	141082			●	●								
51 x 2.8mm Ring	3300	141075								●				
63 x 2.8mm Ring	3300	141071		●						●				
63 x 3.1mm Ring	2200	141073							●					
75 x 3.1mm Ring	2200	141072			●	●	●	●						
90 x 3.1mm Smooth	2200	141070						●						
90 x 3.1mm Ring	2200	141074						●						
63 x 2.8mm Ring	3300	140631							●	●				
63 x 3.1mm Ring	2200	140625							●	●				
75 x 3.1mm Ring	2200	140630							●	●			●	
90 x 3.1mm Smooth	2200	140629						●	●					
90 x 3.1mm Ring	2200	140628			●	●	●							
51 x 2.8mm Ring A2	1100	140624								●			●	●
63 x 2.8mm Ring A2	1100	140626								●			●	●
63 x 2.8mm Ring A4	1100	140632								●			●	●
80 x 3.1mm Ring A2	1100	140627									●		●	●

BATTERY PRODUCT CODE:  
**018880**

FUEL CELL PRODUCT CODE:  
**300348**

GAS POSITIVE PLACEMENT NAILER



## PPNXi

TOOL PRODUCT CODE:  
**019790**

The 1st positive placement nailer on the market provides an efficient and safe way of installing hangers, brackets and straps. The innovative locator probe accurately delivers a hardened twist nail in the precise required location.

### IDEAL USERS

Carpenters and Roofers working on-site, on both New Build and Renovation projects, fixing metal work connectors into wood.



#### FEATURE



#### BENEFIT

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>● Re-engineered nose probe</li> </ul>  | <ul style="list-style-type: none"> <li>● Smaller design to improve accessibility and durability</li> </ul>                          |
| <ul style="list-style-type: none"> <li>● X6 faster than hand nailing the same applications</li> </ul>                   | <ul style="list-style-type: none"> <li>● Reduces fatigue and personal injuries from having to nail in awkward positions</li> </ul>  |
| <ul style="list-style-type: none"> <li>● Nose probe self-locates to allow the nail to fire in the aimed spot</li> </ul> | <ul style="list-style-type: none"> <li>● Difficult to reach areas can now be filled by the PPNXi</li> </ul>                         |
| <ul style="list-style-type: none"> <li>● Quick release magazine</li> </ul>  | <ul style="list-style-type: none"> <li>● Designed to eliminate nail jams and maximise runtime for high volume operations</li> </ul> |
| <ul style="list-style-type: none"> <li>● New battery position for high performing battery</li> </ul>                    | <ul style="list-style-type: none"> <li>● Ensures your tool will work all day. Every day.</li> </ul>                                 |
| <ul style="list-style-type: none"> <li>● Lighter and and better balanced tool</li> </ul>                                | <ul style="list-style-type: none"> <li>● Guarantees all day productivity</li> </ul>   |



#### DID YOU KNOW:

The PPNXi grip has been re-engineered to ensure extra comfort and convenience.



#### CONSUMABLES



#### EUROCODE 5 SERVICE CLASS

- All Paslode framing nails are classified according to Eurocode 5 Service Class 1, 2 and 3 providing a suitable nail for every application.

#### CORROSION REQUIREMENTS OUTLINED IN EUROCODE 5

Service Class 1 INDOORS	Service Class 2 INDOORS NOT HEATED, OUTDOORS PROTECTED	Service Class 3 OUTDOORS, EXPOSED TO WEATHER
BRIGHT		
ELECTRO GALV $\geq 12\mu\text{m}$ and GALV-PLUS <sup>®</sup> $\geq 15\mu\text{m}$		
HOT DIPPED GALVANISED $\geq 55\mu\text{m}$		
STAINLESS STEEL - A2 & A4 (AISI 304)		

- All Paslode nails are hexavalent chromium, cadmium and lead free
- Technical documentation available via the website - [www.paslode.co.uk](http://www.paslode.co.uk)

PPNXi requires ELECTRO GALV Hardened Twist nail which are available in one size

ETA 09/0273 technical approval for 3.4 x 35mm Hardened Twist nails

#### PPNXi NAIL SELECTION GUIDE

NAIL SIZE	QTY	CODE	APPLICATIONS					
			Joist hangers	Truss clips	Connector plates	Strapping	Sole brackets	Z-clips
35 x 3.4mm Twist	1250	141189	●	●	●	●	●	●
35 x 3.4mm Twist	2500	141185	●	●	●	●	●	●



BATTERY PRODUCT CODE:  
**018880**

FUEL CELL PRODUCT CODE:  
**300348**