



## SAFETY DATA SHEET

### EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

According to Regulation (EC) No 1907/2006

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

##### 1.1. Product identifier

Product name EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE  
Product No. 718425, S718425

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

##### 1.3. Details of the supplier of the safety data sheet

Supplier BOSTIK LIMITED  
COMMON ROAD  
STAFFORD  
STAFFORDSHIRE  
ST16 3EH  
+44 1785 272625  
sds.uk@bostik.com

##### 1.4. Emergency telephone number

+44 1785 272650 (24 Hours)

#### SECTION 2: HAZARDS IDENTIFICATION

##### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Not classified.
Human health	Acute Tox. 4 - H332; Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; Resp. Sens. 1 - H334; Skin Sens. 1 - H317; Carc. 2 - H351; STOT SE 3 - H335; STOT RE 2 - H373
Environment	Not classified.

Classification (1999/45/EEC)

Xn; R20, R48/20. Carc. Cat. 3; R40. R42/43. Xi; R36/37/38.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

##### 2.2. Label elements

Contains DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Label In Accordance With (EC) No. 1272/2008



Signal Word

Danger

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

**EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE**

	H351	Suspected of causing cancer.
	H373	May cause damage to organs through prolonged or repeated exposure.
Precautionary Statements	P102	Keep out of reach of children.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P285	In case of inadequate ventilation wear respiratory protection.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements	P202	Do not handle until all safety precautions have been read and understood.
	P271	Use only outdoors or in a well-ventilated area.
	P272	Contaminated work clothing should not be allowed out of the workplace.
	P281	Use personal protective equipment as required.
	P260	Do not breathe vapour/spray.
	P261	Avoid breathing vapour/spray.
	P264	Wash contaminated skin thoroughly after handling.
	P321	Specific treatment (see medical advice on this label).
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P304+341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P313	Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P337	If eye irritation persists:
	P342+311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
	P362	Take off contaminated clothing and wash before reuse.
	P363	Wash contaminated clothing before reuse.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
Supplemental label information	EUH204	Contains isocyanates. May produce an allergic reaction.

**2.3. Other hazards****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE		30-60%
CAS-No.: 101-68-8	EC No.: 202-966-0	Registration Number: 01-2119457014-47
Classification (EC 1272/2008)	Classification (67/548/EEC)	
Acute Tox. 4 - H332	Carc. Cat. 3;R40	
Skin Irrit. 2 - H315	Xn;R20,R48/20	
Eye Irrit. 2 - H319	Xi;R36/37/38	
Resp. Sens. 1 - H334	R42/43	
Skin Sens. 1 - H317		
Carc. 2 - H351		
STOT SE 3 - H335		
STOT RE 2 - H373		

# EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

N,N'-DIMORPHOLINEDIETHYL ETHER		1-5%
CAS-No.: 6425-39-4	EC No.: 229-194-7	
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Xi;R36/38.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

Inhalation

Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. Get medical attention.

Ingestion

DO NOT induce vomiting. Get medical attention immediately.

Skin contact

Promptly flush contaminated skin with soap or mild detergent and water. Promptly remove clothing if penetrated and flush the skin with water. Get medical attention promptly if symptoms occur after washing.

Eye contact

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes and get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

Extinguishing media

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards

Not known.

### 5.3. Advice for firefighters

Protective equipment for fire-fighters

Wear self contained breathing apparatus

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation. Wear personal protective equipment. Wear self contained breathing apparatus.

### 6.2. Environmental precautions

Prevent entry into drains and water courses.

### 6.3. Methods and material for containment and cleaning up

Pick up with vacuum or absorbent solid, store in closed container for disposal.

### 6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

# EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

## 7.2. Conditions for safe storage, including any incompatibilities

Store at moderate temperatures in dry, well ventilated area.

## 7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage Description

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
DIPHENYLMETHANE-4,4'-DI-ISOCYANATE	WEL		0.02 mg/m3(Sen)		0.07 mg/m3(Sen)	

WEL = Workplace Exposure Limit.

Ingredient Comments

WEL = Workplace Exposure Limits

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

Eye protection

Wear splash-proof eye goggles to prevent any possibility of eye contact.

Hygiene measures

Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	White.
Odour	Characteristic.
Solubility	Reacts with water.
Relative density	1.10
Flash point (°C)	295°C

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

# EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

## 10.2. Chemical stability

Stable under normal temperature conditions.

## 10.3. Possibility of hazardous reactions

Not available.

Hazardous Polymerisation

Unknown.

## 10.4. Conditions to avoid

Not known.

## 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Inhalation

Harmful by inhalation. May cause irritation to the respiratory system. May cause sensitisation by inhalation.

Skin contact

Irritating to skin. May cause sensitisation by skin contact.

Eye contact

Irritating to eyes.

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Not regarded as dangerous for the environment.

### 12.1. Toxicity

No data available

### 12.2. Persistence and degradability

Degradability

There are no data on the degradability of this product.

### 12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

### 12.4. Mobility in soil

Mobility:

Semi-mobile.

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects

Not available.

## SECTION 13: DISPOSAL CONSIDERATIONS

General information

This material is classified as special waste as defined by Special Waste Regulations 1996 and must be disposed of by an authorised contractor

# EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

## 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

General The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

## 14.1. UN number

Not applicable.

## 14.2. UN proper shipping name

Not applicable.

## 14.3. Transport hazard class(es)

Transport Labels

No transport warning sign required.

## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

## 14.6. Special precautions for user

Not applicable.

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

## SECTION 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

EU Legislation

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

## 15.2. Chemical Safety Assessment

## SECTION 16: OTHER INFORMATION

General information

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

Information Sources

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision. This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

## EVO-STIK RESIN W POLYURETHANE WOOD ADHESIVE

Issued By Approved EC  
Revision Date December 2014  
Revision 3  
Date September 2010

### Risk Phrases In Full

R20 Harmful by inhalation.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R36/38 Irritating to eyes and skin.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R40 Limited evidence of a carcinogenic effect.  
R42/43 May cause sensitisation by inhalation and skin contact.

### Hazard Statements In Full

H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H373 May cause damage to organs <<Organs>> through prolonged or repeated exposure.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.