



ULTIMA+ dB



OFFICE – Trade Center Weena Plaza (NL)
ULTIMA+ dB SL2

ULTIMA+ dB not only offers a finely textured and durable surface with a brighter “blue-white” colour for high light reflectance, but is also C2C Bronze certified and provides higher levels of sound attenuation performance for improving the privacy between adjacent spaces.

Key features

- Eliminates the need for sound barriers in closed offices
- Very high light reflectance: 87%
- Better finish and more durable edges
- C2C Bronze certified / ISO 5 / A+
- 30 year system guarantee

Application areas

Ideal for individual / private offices.




Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

EDGE DETAIL	BOARD	TEGULAR	MICROLOOK 90	SL2
THICKNESS (mm)	19	19	19	23
MODULES (mm)	600 x 600 7688M 675 x 675 7689M 1200 x 600 7690M	600 x 600 7695M 675 x 675 7696M	600 x 600 7697M 675 x 675 7698M	1500 x 300 7691M 1800 x 300 7692M 2500 x 300 7693M
SUSPENSION SYSTEMS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²	System Z - T-Bar System Z - Z-Bar System Z Corridor - T-Bar System Z Corridor - Z-Bar

COLOURS



Global White

SUSTAINABILITY



BRONZE



36-43¹






A+



E1


¹ Depends on thickness, edge detail and size of tile.

ACOUSTICS



	D _{nfw}	R _w	α _w	Class	NRC	Hz α _p						
						125	250	500	1000	2000	4000	
• Board, Tegular, MicroLook 90	41 dB	21 dB	0.60(H)	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95	
• SL2	43 dB	-	0.60(H)	C	0.55	0.35	0.40	0.50	0.60	0.75	0.85	


FIRE REACTION





EEA Euroclass A2-s1, d0
EN 13501-1


RUS KM1 (G1, V1, D1, T1)
FZ 123



OTHER PERFORMANCES & FEATURES


87% 


λ = 0.067 W/m K 
EN 12667 & ISO 8301


95% RH 

7.6 kg/m² (Board, Tegular, MicroLook 90)
9.1 kg/m² (SL2) 

ISO 5 
ISO 14644-1 







30YEAR
system guarantee

BIM
READY

CUSTOM OPTIONS



Dimensions