

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
 Trade name : COLORFILL  
 Type of product : adhesives  
 Product group : Trade product

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Main use category : Professional use  
 Use of the substance/mixture : Adhesives, binding agents  
 Function or use category : Adhesives, binding agents

**1.2.2. Uses advised against**

Restrictions on use : Adhesives, sealants

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

IPS Adhesives Ltd  
 New York Way  
 NE27 0QF Newcastle upon Tyne – Tyne & Wear  
 United Kingdom  
 T +44 (0)191 259 0033 - F +44 (0)191 257 4525  
[sales@unika.co.uk](mailto:sales@unika.co.uk) - [www.unika.co.uk](http://www.unika.co.uk)

**Only Representative**

Ricardo Nederland BV B.V.  
 Catharijnesingel 33 3511 GC Utrecht  
 Netherlands

**1.4. Emergency telephone number**

Emergency number : ChemTel: 001 813-248 0573 (International)  
 ChemTel 24 hrs/7 days

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2 H225  
 Serious eye damage/eye irritation, Category 2 H319  
 Specific target organ toxicity – Single exposure, Category 3, Narcosis H336  
 Full text of H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger  
 Contains : ETHYL METHYL KETONE, PROPAN-2-OL, ACETONE  
 Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.  
 H319 - Causes serious eye irritation.  
 H336 - May cause drowsiness or dizziness.

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P271 - Use only outdoors or in a well-ventilated area. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

PBT: not yet assessed  
vPvB: not yet assessed

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
PROPAN-2-OL	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0	≥ 10 – < 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ACETONE	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	≥ 10 – < 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ETHYL METHYL KETONE	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3	≥ 10 – < 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.
First-aid measures after skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing). May cause shortness of breath, tightness of the chest, a sore throat and cough.
-----------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Symptoms/effects after skin contact	: irritation (itching, redness, blistering).
Symptoms/effects after eye contact	: redness, itching, tears.
Symptoms/effects after ingestion	: Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Carbon dioxide. Carbon monoxide. Toxic fumes may be released.

### 5.3. Advice for firefighters

Precautionary measures fire	: Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Eliminate all ignition sources if safe to do so.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Do not handle until all safety precautions have been read and understood.
------------------	-----------------------------------------------------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Keep upwind. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene.
Measures in case of dust release	: Do not inhale dusts, particulates and spray mist when using this preparation.

#### 6.1.2. For emergency responders

Protective equipment	: Use self-contained breathing apparatus and chemically protective clothing.
Emergency procedures	: Stop leak if safe to do so. Cover spill with non combustible material, e.g.: sand/earth.

### 6.2. Environmental precautions

Do not allow to enter drains or water courses. Do not allow product to spread into the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Absorb spilled material with sand or earth.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling	: Avoid contact with skin, eyes and clothing. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station.
Handling temperature	: 13 – 27 °C
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep container tightly closed.
Incompatible products	: Oxidizing agent. Strong acids.
Incompatible materials	: Sources of ignition.
Storage temperature	: 13 – 27 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Keep only in original container.
Packaging materials	: Keep only in the original container in a cool, well-ventilated place away from combustible materials.

#### 7.3. Specific end use(s)

Adhesives, Sealants.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

ETHYL METHYL KETONE (78-93-3)	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	2-Butanone # 2-Butanon
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Метилетилкетон (бутанон)
OEL TWA	590 mg/m <sup>3</sup>
OEL STEL	885 mg/m <sup>3</sup>
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Butanon; etil-metil-keton
GVI (OEL TWA) [1]	600 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	200 ppm

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
KGVI (OEL STEL)	900 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	300 ppm
Remark	Direktiva: 2000/39/EZ
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	2-Butanon (Methylethylketon)
PEL (OEL TWA)	600 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	200 ppm
NPK-P (OEL C)	900 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	301 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Butanon (Ethylmethylketon; MEK; Methylethylketon)
OEL TWA [1]	145 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
Regulatory reference	BEK nr 290 af 13/02/2021
<b>Estonia - Occupational Exposure Limits</b>	
Local name	2-butanoon
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	2-Butanoni
HTP (OEL TWA) [1]	60 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	20 ppm
HTP (OEL STEL)	300 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	100 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Méthyléthylcétone, 2-Butanone (Butanone)
VME (OEL TWA)	600 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	200 ppm
VLE (OEL C/STEL)	900 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	300 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Butanon
AGW (OEL TWA) [1]	600 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	1(!)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Gibraltar - Occupational Exposure Limits</b>	
Local name	Butanone
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Μεθυλοαιθυλο-κετόνη
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
Local name	METIL-ETIL-KETON
AK (OEL TWA)	600 mg/m <sup>3</sup>
CK (OEL STEL)	900 mg/m <sup>3</sup>
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methyl ethyl ketone (MEK)
OEL TWA [1]	600 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Chemical Agents Code of Practice 2020

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
<b>Italy - Occupational Exposure Limits</b>	
Local name	Butanone
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
Local name	2-Butanons (metiletilketons, etilmetilketons)
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA [ppm]	67 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Butanonas (metiletilketonas)
IPRV (OEL TWA)	600 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	200 ppm
TPRV (OEL STEL)	900 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	300 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Luxembourg - Occupational Exposure Limits</b>	
Local name	Butanone
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Mémorial A N° 684 de 2018 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
<b>Malta - Occupational Exposure Limits</b>	
Local name	Butanone
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	2-Butanon
TGG-8u (OEL TWA)	590 mg/m <sup>3</sup>

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
TGG-15min (OEL STEL)	900 mg/m <sup>3</sup>
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021
<b>Poland - Occupational Exposure Limits</b>	
Local name	Butan-2-on
NDS (OEL TWA)	450 mg/m <sup>3</sup>
NDSCh (OEL STEL)	900 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Metiletilcetona (MEK) (2-Butanona)
OEL TWA [ppm]	200 ppm
OEL STEL [ppm]	300 ppm
Remark	IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	2 Butanonă/Etil metil cetonă/Butanonă
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Serbia - Occupational Exposure Limits</b>	
Local name	бутанон; метил-етил-кетон
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Remark	EU* – напомена да се ради о хемијским материјама за које су утврђене индикативне граничне вредности изложености према Директиви 2000/39/ЕЗ (прва листа)
Regulatory reference	ПРАВИЛНИК о превентивним мерама за безбедан и здрав рад при излагању хемијским материјама („Службени гласник РС”, бр. 106/09 и 117/17)
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Butanón (etylmetylketón)
NPHV (OEL TWA) [1]	600 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL STEL)	900 mg/m <sup>3</sup>
NPHV (OEL STEL) [ppm]	300 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)



# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	butanon (etilmetilketon)
OEL TWA	600 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	900 mg/m <sup>3</sup>
OEL STEL [ppm]	300 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 78/2019 z dne 20.12.2019
<b>Spain - Occupational Exposure Limits</b>	
Local name	Metiletilcetona (Butanona)
VLA-ED (OEL TWA) [1]	600 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	900 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	300 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Metyletylketon (MEK)
NGV (OEL TWA)	150 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	900 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	300 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Butan-2-one (methyl ethyl ketone)
WEL TWA (OEL TWA) [1]	600 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	899 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	300 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Metýletýlketón (bútanón, etýlmetýlketón, MEK)
OEL TWA	145 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	900 mg/m <sup>3</sup>

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>ETHYL METHYL KETONE (78-93-3)</b>	
OEL STEL [ppm]	300 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Butanon (Metyletylketon)
Grænseverdi (OEL TWA) [1]	220 mg/m <sup>3</sup>
Grænseverdi (OEL TWA) [2]	75 ppm
Regulatory reference	FOR-2020-04-06-695
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	2-Butanone / 2-Butanon [Ethylmethylketon, Methylethylketon (MEK)]
MAK (OEL TWA) [1]	590 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	590 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	200 ppm
Critical toxicity	VRS, SN / OAW, NS
Notation	R, SS <sub>C</sub> , B / H, SS <sub>C</sub> , B
Remark	INRS, NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2021
<b>PROPAN-2-OL (67-63-0)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1000 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Изопропилов алкохол
OEL TWA	980 mg/m <sup>3</sup>
OEL STEL	1225 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Пропан-2-ол; izopropil-alkohol; izopropanol
GVI (OEL TWA) [1]	999 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	400 ppm
KGVI (OEL STEL)	1250 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	500 ppm

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PROPAN-2-OL (67-63-0)</b>	
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	2-Propanol (Isopropanol; Izopropylalkohol)
PEL (OEL TWA)	500 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	200 ppm
NPK-P (OEL C)	1000 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	400 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
OEL TWA [1]	490 mg/m <sup>3</sup>
OEL TWA [2]	200 ppm
Regulatory reference	BEK nr 290 af 13/02/2021
<b>Estonia - Occupational Exposure Limits</b>	
Local name	2-propanool (isopropüülalkohol, isopropanool)
OEL TWA	350 mg/m <sup>3</sup>
OEL TWA [ppm]	150 ppm
OEL STEL	600 mg/m <sup>3</sup>
OEL STEL [ppm]	250 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
<b>Finland - Occupational Exposure Limits</b>	
Local name	2-Propanoli
HTP (OEL TWA) [1]	500 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	620 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	250 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Alcool isopropylique
VLE (OEL C/STEL)	980 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Propan-2-ol
AGW (OEL TWA) [1]	500 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	2(II)

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PROPAN-2-OL (67-63-0)</b>	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Greece - Occupational Exposure Limits</b>	
Local name	Ισοπροπυλική αλκοόλη
OEL TWA	980 mg/m <sup>3</sup>
OEL TWA [ppm]	400 ppm
OEL STEL	1225 mg/m <sup>3</sup>
OEL STEL [ppm]	500 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
Local name	IZOPROPIL-ALKOHOL
AK (OEL TWA)	500 mg/m <sup>3</sup>
CK (OEL STEL)	1000 mg/m <sup>3</sup>
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Isopropyl alcohol [Propan-2-ol]
OEL TWA [2]	200 ppm
OEL STEL [ppm]	400 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
OEL TWA	350 mg/m <sup>3</sup>
OEL STEL	600 mg/m <sup>3</sup>
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	2-propanolis (izopropanolis, izopropilo alkoholis)
IPRV (OEL TWA)	350 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	150 ppm
TPRV (OEL STEL)	600 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	250 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Poland - Occupational Exposure Limits</b>	
Local name	Propan-2-ol (izopropylowy alkohol)
NDS (OEL TWA)	900 mg/m <sup>3</sup>
NDSch (OEL STEL)	1200 mg/m <sup>3</sup>

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PROPAN-2-OL (67-63-0)</b>	
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	2-Propanol (isopropanol ou álcool isopropílico)
OEL TWA [ppm]	200 ppm
OEL STEL [ppm]	400 ppm
Remark	A4 (Agente não classificável como carcinogénico no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	Alcool izopropilic/2-Propanol
OEL TWA	200 mg/m <sup>3</sup>
OEL TWA [ppm]	81 ppm
OEL STEL	500 mg/m <sup>3</sup>
OEL STEL [ppm]	203 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Izopropylalkohol (propán-2-ol)
NPHV (OEL TWA) [1]	500 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL STEL)	1000 mg/m <sup>3</sup>
NPHV (OEL STEL) [ppm]	400 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	propan-2-ol (izopropilalkohol; izopropanol)
OEL TWA	500 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
OEL STEL	1000 mg/m <sup>3</sup>
OEL STEL [ppm]	400 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost)
Regulatory reference	Uradni list RS, št. 78/2019 z dne 20.12.2019
<b>Spain - Occupational Exposure Limits</b>	
Local name	Isopropanol (Alcohol isopropílico)
VLA-ED (OEL TWA) [1]	500 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1000 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	400 ppm

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>PROPAN-2-OL (67-63-0)</b>	
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: <a href="http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas">http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas</a> Base de datos de productos fitosanitarios <a href="http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf">http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf</a> ).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Isopropanol
NGV (OEL TWA)	350 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	600 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	250 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	2-Própanól (ísóprópanól, ísóprópylalkóhól, sec-própylalkóhól)
OEL TWA	490 mg/m <sup>3</sup>
OEL TWA [ppm]	200 ppm
Remark	H (efnið getur auðveldlega borist inn í líkamann gegnum húð)
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	2-propanol (Isopropanol)
Grenseverdi (OEL TWA) [1]	245 mg/m <sup>3</sup>
Grenseverdi (OEL TWA) [2]	100 ppm
Regulatory reference	FOR-2020-04-06-695
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	2-Propanol / 2-Propanol [iso-Propylalkohol, Isopropanol, Isopropylalkohol]
MAK (OEL TWA) [1]	500 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	200 ppm
KZGW (OEL STEL)	1000 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	400 ppm
Critical toxicity	VRS, Foie, SNC, Yeux / OAW, Leber, ZNS, Auge
Notation	SSc, B / SSc, B

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### PROPAN-2-OL (67-63-0)

Remark	INRS, NIOSH
Regulatory reference	www.suva.ch, 01.01.2021

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure that there is a suitable ventilation system.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

##### 8.2.2.2. Skin protection

#### Skin and body protection

Type	Standard
Disposable gloves	EN 374-2

##### Hand protection:

Nitrile rubber gloves

#### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	2 (> 30 minutes)	< 0.7	2 (< 1.5)	EN ISO 374

##### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Characteristic odour.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 80 °C
Flash point	: 0 °C
Auto-ignition temperature	: 465
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.979 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions of use.

### 10.3. Possibility of hazardous reactions

Stable under normal conditions of use.

### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Strong acids. Oxidizing agent.

### 10.6. Hazardous decomposition products

May liberate toxic gases.



# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

PROPAN-2-OL (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)

ACETONE (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rat	> 15800 mg/kg

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

ETHYL METHYL KETONE (78-93-3)	
STOT-single exposure	May cause drowsiness or dizziness.

PROPAN-2-OL (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.

ACETONE (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

ETHYL METHYL KETONE (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

PROPAN-2-OL (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### COLORFILL

PBT: not yet assessed

vPvB: not yet assessed

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Industrial waste.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1133	UN 1133	UN 1133	UN 1133	UN 1133
<b>14.2. UN proper shipping name</b>				
Adhesives	Adhesives	Adhesives	Adhesives	Adhesives
<b>Transport document description</b>				
UN 1133 Adhesives, 3, II, (D/E)	UN 1133 Adhesives, 3, II	UN 1133 Adhesives, 3, II	UN 1133 Adhesives, 3, II	UN 1133 Adhesives, 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Transport category (ADR) : 2  
Tunnel restriction code (ADR) : D/E

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

#### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see [https://ec.europa.eu/home-affairs/system/files/2021-11/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf)

#### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

### Netherlands

ABM category : A(4) - low hazard for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

### Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F <Flam. Liq. 2>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### Switzerland

Storage class (LK) : LK 3 - Flammable liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

## SECTION 16: Other information

### Indication of changes:

Revision - See : \*.

Abbreviations and acronyms:	
CAS-No.	Chemical Abstract Service number
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
ED	Endocrine disrupting properties
EN	European Standard

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:	
IARC	International Agency for Research on Cancer
IOELV	Indicative Occupational Exposure Limit Value
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances
vPvB	Very Persistent and Very Bioaccumulative
VOC	Volatile Organic Compounds
WGK	Water Hazard Class

Data sources : ECHA (European Chemicals Agency).

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

# COLORFILL

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.