AR2 SHXSMFF C

ARTISAN Shower Range

Artisan Thermostatic Surface Mounted

Bar Shower Valve with Adjustable Riser & Fast Fit Connections



Features:

- TMV2 thermostatic control for a higher level of performance and protection
- Eco feature on flow control (can be over-ridden)
- Supplied with our wallmount 10 fixing kit for easier retro installation
- Rub clean handset
- Adjustable fixing brackets on riser rail

Product Certifications:




WRAS Certificate No: 1711005 WRAS Expiry Date: 30/11/2022

For more products, visit our website: <u>Contemporary</u>



Specification					
Style:	Contemporary				
Finish/Colour:	Chrome				
Main Construction Material:	Brass				
No of Controls:	2				
Shower Type:	Bar Shower				
Shower Head Type:	Single Function Handset				
Valve/Cartridge Type:	Exposed				
Maximum Hot Water Supply Temperature °C:	60°C - Pre-set to 38°C				
Dynamic Pressure Range: (bar)	5				
Maximum Static Pressure: (bar)	10				
Plumbing System Suitability:	All				
Working Pressure Range:	Min 0.1 Bar, Max 5.0 Bar				
Flow Rate: (I/min @ 3 bar)	25.5				
Connection Inlet:	15mm compression				
Connection Outlet:	G 1/2" BSP				
Isolation Valve Included:	No				
Check Valve Included:	Yes				

Dimensions (measurements in mm)



Flow Rates (I/min)							
System Pressure (bar)	0.2	0.5	1	2	3	5	
Through Handset (mixed)		5.5	8.3	12	14	14	
With Flow Regulators Fitted		10	14	14	14	14	
Without Flow Regulators Fitted	5	9.4	14.2	20.8	25.5	33.2	

TECHNICAL DATA SHEET



