

Mira Platinum

Digital Mixer



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Experience ultimate control at your fingertips with our easy to use, wireless Platinum controller.

Product Information

Description	Colour	Product No.
Mira Platinum Shower, Rear Fed (High Pressure/Combi)	Chrome	1.1666.200
Mira Platinum Shower, Rear Fed (Pumped for Gravity)	Chrome	1.1666.201
Mira Platinum Shower, Ceiling Fed (High Pressure/Combi)	Chrome	1.1666.001
Mira Platinum Shower, Ceiling Fed (Pumped for Gravity)	Chrome	1.1666.002
Mira Platinum Shower, Valve & Controller Only (HP/Combi)	Chrome	1.1666.003
Mira Platinum Shower, Valve & Controller Only (Pumped)	Chrome	1.1666.004

Features & Benefits

Temperature control

- Thermostatic temperature stability with digital intelligence
- Maximum temperature setting for increased safety

Easy to fit & maintain

- Rear and ceiling fed options available for all types of installation
- Built in push-fit isolators
- Large long-life filters and replaceable cartridge

For your customer

- Adjust your temperature at the touch of a button, and rotate the controller to fine tune your flow
- Warm-up mode pauses at your ideal temperature so it's ready when you are
- Digital clock display with 5 minute timer when the Eco function is selected
- Includes Mira 360 showerhead with Mira Flipstream™ technology - 1 flip action, 4 unique sprays
- Turn your shower on before you get in with an optional secondary controller, useable from up to 10m away



MIRA PLATINUM REAR FED

MIRA PLATINUM CEILING FED

Product Specification

Tech Details

Installation Units & Fittings

Water Entry Points - Back, Rear Fed; Top, Ceiling Fed
 Inlet Connections: 15mm Push Fit (supplied) or 15mm compression
 Data Connection to Digital Mixer: Wireless

Digital Mixer

Inlet Connections: 15mm Push Fit (supplied) or 15mm compression
 Outlet connection: 15mm push fit (supplied)
 Data Connection to control unit and fittings: Wireless
 Supply voltage: 230v +10%
 Supply rating: 3 amp

Supply Conditions

Cold water range: 1°C-20°C
 Hot water range: 55°C-65°C
 Minimum maintained pressure:
 Pumped: 0.01 bar (10cm head); High Pressure: 0.5 bar (5 metre head)
 Maximum maintained pressure:
 Pumped: 1.0 bar (10 metre head); High Pressure: 5.0 bar (50 metre head)
 Maximum static pressure:
 Pumped: 1.0 bar (10 metre head); High Pressure: 10.0 bar (100 metre head)

Performance

Flow rate: up to 16 l/min at 0.1 bar (Pumped); 1 bar (High Pressure)
 Temperature stability: ± 1°C

Safety Features

Factory set to safe max temp: Factory set at 45°C
 Automatic shutdown: Yes

Approvals

WRAS approved
 KIWA UK approved product



Dimensions

