

# Dryshield® Cream

## Product Description

**Dryshield® Cream** is a breathable, salt-resistant and water-repellent cream that acts as a primer for Drygrip™ Adhesive. It forms part of the Dryzone System for faster replastering after rising damp treatment.

When applied to walls contaminated with groundwater salts from rising damp, **Dryshield® Cream** functions by hydrophobing the surface and weakening the crystallisation strength of salts which may form in or at the masonry surface. The wall can dry out and potentially damaging salts are kept away from plasterboard and other decorative finishes. For internal use only.



## Benefits

- Breathable
- Deeply penetrates brick, stone and mortar to form a durable bond
- Long-lasting formulation
- Quick, one coat application by brush, roller or spray

## Properties

Appearance	White
Density	0.9 g/cm <sup>3</sup>
Size(s) & Packaging	1 litre tins, 3 litre and 5 litre plastic buckets
Shelf Life	12 months
Water Solubility/ Miscibility	Completely miscible at 20°C
Coverage	3 – 4 m <sup>2</sup> per 1 litre tin <sup>[1]</sup> 15 – 20 m <sup>2</sup> per 5 litre bucket <sup>[1]</sup> 9 – 12 m <sup>2</sup> per 3 litre bucket <sup>[1]</sup>
Storage	Store in a cool, well ventilated area. Keep container tightly closed. Protect from frost



## Application Information

### Preparation

All surfaces must be clean, sound and free of dust or laitance.

### Application

1. Apply **Dryshield® Cream** to wall in a single coat, ideally using a large soft brush.
2. Make sure any holes and cracks are filled with cream and that all areas are coated evenly.
3. Allow **Dryshield® Cream** to soak into the substrate for at least 30 minutes. Do not leave for more than 24 hours before applying Drygrip™ Adhesive.

For full application instructions see the Dryzone® System Application Guidelines. Patch trials are recommended before large scale application. If in doubt, please contact our Technical Department for advice.

## Other Information

**Dryshield® Cream** does not have a hazard classification. For more information see the Safety Datasheet (SDS).

**Dryshield® Cream** is produced in accordance with ISO 9001 and ISO 14001 quality and environmental management systems.

*Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.*

<sup>[1]</sup> The coverage rate will vary depending upon the roughness and absorbency of the surface, use as a guide only.