



TECHNICAL INFORMATION

COLD LAY MACADAM

Product Data Sheet

DESCRIPTION

Drive Patch Cold Lay Macadam is a ready to use, easy, cost-effective product that can be used straight from the bag for a quick solution for repairs to pathways and drives.

USES

- For use to repair a driveway.
- To repair and widen pathways.
- To repair potholes.
- Temporary ramps.

SPECIAL PROPERTIES

- Easy to use, no previous experience is necessary.
- No specialist tools or equipment are required.
- Product is suitable for base or wearing course.

PREPARATION & APPLICATION GUIDES

- Ensure the area where the **Drive Patch Cold Lay Macadam** is to be used is dry and firm enough to support the weight of a car under normal conditions.
- Sweep the area and remove all weeds.
- Before overlaying concrete or paving, spray, or brush on a tack coat of bitumen emulsion (edging & Jointing Spray is recommended) at a rate of about 0.5litres/m², to help prolong the life of the repair, especially if prone to freeze/thaw conditions.
- Use a spade, rake, or trowel to spread the **Drive Patch Cold Lay Macadam** to the required thickness.
- To achieve good compaction, use a roller or, alternatively, you can use a heavy, flat object for 'tamping' to achieve similar.
- To stop the product sticking to the tool wet the roller or tamper frequently.
- To help prevent 'picking up' of the fresh material as it sets brush a little dry sand or dust over the surface after compaction. This is particularly helpful when the weather is warmer.

- If you are repairing deep potholes (greater than 30mm) you need to lay the **Drive Patch Cold Lay Macadam** in two stages.
- You must thoroughly compact the first layer before spreading the next layer and compact to bring the finished surface to the required level.
- It is not advised to place heavy and sharp objects on the newly laid surface, such as caravan legs, jockey wheels and other similar high loadings.
- **Drive Patch Cold Lay Macadam** is not recommended for use outside temperatures below 5°C or when the area working on is very wet.
- Clean all equipment and tools with water prior to the material setting.

TYPICAL COVERAGE

One bag of **Drive Patch Cold Lay Macadam** will cover approximately 0.4m² at 30mm when compacted.

PLEASE NOTE:

- After prolonged storage, it may be necessary to expose the bag of the **Drive Patch Cold Lay Macadam** to direct sunlight for 1-2 hours prior to opening to loosen the material and restore workability.
- To improve the workability of the **Drive Patch Cold Lay Macadam** if the outside temperature is above 10°C (50°F).
- For a better surface finish, rolling or tamping will need to be applied to the surface.
- The material may be susceptible to marking during early life and warm weather conditions.
- The time taken by the **Drive Patch Cold Lay Macadam** to harden fully will depend on the degree of compaction and temperature.



The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Aggregates R Us endeavour to ensure that the information given is accurate but accept no liability for its use or its suitability for application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.



PACKAGING & STORAGE

Drive Patch Cold Lay Macadam is available in large bags. Always keep the bag sealed when not in use.

QUALITY CONTROL

All Aggregates R Us products are factory blended, tested and packaged to quality control procedure in accordance with BS EN ISO 9001.

SAFETY & HEALTH WARNING RISKS

Health and safety advice, for additional information please refer to the Material Safety Data Sheet.

- Skin contact: The product is very sticky.
- If the products make contact with the skin use cleanser followed by soap.
- Fumes from **Drive Patch Cold Lay Macadam** are unlikely to be hazardous when laid in open air situations, but there may be a risk to health by continuous inhalation of high vapour concentrations which might arise in confined or semi-confined spaces.
- Do not place heavy and sharp objects on the newly laid surface.
- Protect from caravan legs, jockey wheels and other similar high loadings.

SAFETY

- Respiratory Protection: Suitable masks if dust/fumes are present in significant quantities.
- Hand Protection: Gloves are recommended.
- Eye Protection: Goggles are recommended.
- Skin Protection: Overalls are recommended.

INFORMATION, PRICES & ORDERING

For technical information, pricing and to place orders please contact us as follows:

Tel: 01302 770918

Email: sales@aggsrus.co.uk

Website: www.aggregatesrus.co.uk

Address: Aggregates R Us, Meteor House, Finningley DN9 3GA

