

# grey sandstone

classicstone calibrated 24mm


## PROJECT PACK

Traditional natural stone flags.

### 560 SERIES PROJECT PACK CONFIGURATION

NOMINAL SIZE (mm)	No. PER PACK
840 x 560	12
560 x 560	12
560 x 420	12
560 x 270	13
270 x 270	13

When laid, a Project Pack covers an area of approximately 15.84m<sup>2</sup>



Nominal Pack Weight 780kg.

CE

Natural Paving Products (UK) Ltd  
Belton Rd Sandtoft Doncaster  
North Lincolnshire DN8 5SX England  
13

EN 1341:2012

Natural Stone Slabs  
Promenade Quartzitic Sandstone  
Kota, Rajasthan, India  
For external pedestrian areas

PRFGCA56MINIPP

RELEASE OF DANGEROUS SUBSTANCES	NPD
BREAKING STRENGTH AS	
- flexural strength (EN 12372) as (lower expected value)	24.5MPa
SLIPPERINESS	
- slip resistance wet (EN 14231)	51
SKID RESISTANCE AS	
- skid resistance according to MS method xx	NPD
DURABILITY	
- of flexural strength against: freeze/thaw	29.3/30.1 MPa
Freeze-thaw with de-icing salts	NPD
- of slip resistance	NPD
- of slip resistance	NPD

**Installing Instructions** - As natural stone varies in colour and texture ensure you have enough product to complete the project and always mix from all the packs during installation. Please visit [www.naturalpaving.co.uk](http://www.naturalpaving.co.uk) for further details.

**Health & Safety Information** - We recommend when moving pieces of 25kg that more than one person helps in completing the lift or that suitable lifting equipment is used.

We would also recommend that appropriate footwear and gloves are worn when handling our products.

When cutting our products either with chisels or rotary disk cutters it is essential that suitable eye protection is worn. Always ensure that suitable respiratory protection is worn to avoid inhalation of dust particles from high speed cutting devices. Please visit [www.naturalpaving.co.uk](http://www.naturalpaving.co.uk) for further details.