

TECHNICAL DATA SHEET

TRAVIS PERKINS READY MIXED FINE SURFACE FILLER

Dec Choice Fine Surface Filler is used for smaller cracks, where standard ready mixed filler may not be suitable, although it may be for larger repairs as well. Dries super white. May be sanded when dry, although this is often unnecessary, due to its very smooth consistency. Can also be used externally, provided repairs are painted or varnished after drying.

USES

A ready to use, super smooth filler, ideal for repairs to walls and ceilings, doors, windows, skirting etc, where a perfect finish is required. Suitable for interior and exterior use, and can be used to fill deeper cavities. Suitable for use on brickwork, stone, plaster, wood and many other materials.

COLOURS: Opaque white

PACKAGING: 1kg packed 1 x 6

PREPARATION

Ensure surfaces are clean, dry and dust free.

APPLICATION

Apply in a thin layer using a filling knife or spatula, pressing into cavities. If a deeper repair is required, fill up the filler in thinner layers, or use a general purpose filler, followed by the fine surface filler. For a perfect finish, fill slightly proud of the surrounding surface and use fine sandpaper to blend in the repair.

FINISHING

Exterior repairs should be over painted with an oil based paint to protect from weathering. Clean tools with water before filler sets hard. After use ensure the lid is firmly replaced. Protect from frost.

HEALTH & SAFETY

Do not consume. Keep away from children and animals. If filler comes into contact with skin, wash with warm water before filler dries.

TRAVIS PERKINS READY MIXED FINE SURFACE FILLER TECHNICAL DATA SHEET

LIMITATIONS

Do not use on surfaces regularly under water. An adhesion test prior to application is recommended. It is the users responsibility to determine suitability.

LIABILITY

The information given is the result of our tests and experience and is believed to be accurate and reliable. However as Siroflex Limited cannot know all the uses its products may be put to, it is the user's responsibility to determine suitability of use.

TECHNICAL DATA

Specification

Physical state	Paste
Form/ colour	Opaque
Odour	Mild
Specific gravity	1.540 +/- 0.05
Viscosity	2800 – 3300 Poise
pH	7.2 – 8.0
Solubility in water	Miscible