



Smeed Dean London Stock

Product Technical Information Sheet Wienerberger Code 24230010 **Production Plant** Smeed Dean Soft Mud Moulded Stock Manufacture Configuration Frogged Yellow Multi Colour Flat/Sanded Appearance 215 x 102.5 x 65 Work Size (mm)

500 No.


2.0



Technical Properties to BS EN 771-1


Individual Dry Brick Weight (kg)

Size Tolerance (Mean/Range)	T1/R1
Gross Dry Density (kg/m³/Tolerance)	1380 (D1)
Compressive Strength (N/mm²)	≥15
Thermal Conductivity (W/(m·K)) $\lambda_{10,dry,unit}$ value (EN 1745 tabulated: S1)	P=90% 0.51
Durability Designation	F2
Water Absorption (%)	≤22
Initial Rate of Water Absorption (kg/(m²·min))	Min. 1.2 Max. 4.2
Active Soluble Salts	S2
Reaction to Fire	Class A1



Pack Quantity

Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Wienerberger Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.





1000+ products to choose from



Expert help and advice



Comprehensive Design Services



Technical Support

